Sustainable Water Management Initiative: Advisory Committee

Presentation Title: Current WMA Permit Conditions

Flow Levels/Habitat Categories in Permit Application Reviews

Presented By: Duane LeVangie

Department of Environmental Protection

Date of Presentation: 22 March 2011

The following presentation is offered for discussion purposes only and does not necessarily represent current statute, regulation, or policy positions of the Commonwealth of Massachusetts unless specifically acknowledged.

This presentation is not to be cited as a reference. It's purpose is to foster open and broad discussion of the issues as well as help assure public awareness of the discussions as of the date of the presentation.

STREAM FLOW CRITERIA AND PERMITTING SCENARIOS

Sustainable Water Management Initiative Advisory Committee
March 22, 2011


SWMI Advisory Committee

Disclaimer

- The following presentation is offered for discussion purposes only and does not necessarily represent current statute, regulation, or policy positions of the Commonwealth of Massachusetts unless specifically acknowledged.
- This presentation is not to be cited as a reference. It's
 purpose is to foster open and broad discussion of the issues
 as well as help assure public awareness of the discussions
 as of the date of the presentation.

Agenda

- Statewide overview
- WMA existing permit conditions
- Streamflow criteria
- WMA proposed Tier Permit Review
- Tier review scenarios (case example)
- Mitigation conditions
- Questions for consideration



- 1. Surface water and groundwater source protection
- 2. Firm yield analysis for PWS surface water impoundments
- 3. Wetlands and vernal pool monitoring
- 4. Performance standard: 65 residential gallons/capita/day





- 6. Seasonal limits on nonessential outdoor water use
 - Calendar or stream flow trigger



- 7. Water conservation requirements
 - Water audits, leak detection, metering, pricing, residential and public sector including municipal buildings
- 8. Water withdrawal increases that exceed baseline
 - Offset Feasibility Study



Performance Standard Residential Gallons Per Capita Day (RGPCD) Water Use

- The performance standard for RGPCD is 65 gallons.
- 2 full calendar years to meet the standard.
- Choice to file an individual RGPCD Plan of their own creation, or may adopt the RGPCD Functional Equivalence Plan that includes MassDEP's Best Management Practices (BMPs)
- Permittee unable to meet 65 RGPCD within 5 years must implement MassDEP's Functional Equivalency Plan.

MassDEP's RGPCD Functional Equivalence Plan Requires

- Adoption of all three (3) items from the Individual Plan.
 - 1. a program that provides water saving devices at cost
 - A program that provides incentives for the purchase of low flow water use appliances
 - 3. the adoption and enforcement of an ordinance to require the installation of climate-related control technology on all automatic irrigation systems
- Compliance with permit conditions including the Seasonal Limits on Nonessential Outdoor water use.
- Use of increasing block rates or a seasonal water rate structure.
- Implementation of monthly or quarterly billing

- 1. Surface water and groundwater source protection
- 2. Firm yield analysis for PWS surface water impoundments
- 3. Wetlands and vernal pool monitoring
- 4. Performance standard: 65 residential gallons/capita/day





- 6. Seasonal limits on nonessential outdoor water use
 - Calendar or stream flow trigger



- 7. Water conservation requirements
 - Water audits, leak detection, metering, pricing, residential and public sector including municipal buildings
- 8. Water withdrawal increases that exceed baseline
 - Offset Feasibility Study

Performance Standard Unaccounted-For-Water (UAW)

- The performance standard for UAW is 10% of overall withdrawal.
- 2 full calendar years to meet the standard.
- Choice to file an individual UAW Plan of their own creation, or may adopt the UAW Functional Equivalence Plan that includes MassDEP's Best Management Practices (BMPs)
- Permittee unable to meet 10% UAW within 5 years must implement MassDEP's Functional Equivalency Plan.

UAW Functional Equivalence Plan BMPs

- Analyze the failure to meet the performance standard.
- Develop a schedule of actions to meet the performance standard
- Annually describe the actions taken to address the failure to meet the performance standard.
- Complete a water audit and leak detection survey of the entire system within one year.
- Conduct sufficient repairs to reduce by 75% (volume) all leaks detected in the survey; then conduct additional repairs as necessary to reduce UAW to 10% or less.
- Implement a program for the inspection, evalution, repair, replacement and calibration of all water meters.
- Implement monthly or quarterly billing.
- Implement a full cost water pricing structure.

- 1. Surface water and groundwater source protection
- 2. Firm yield analysis for PWS surface water impoundments
- 3. Wetlands and vernal pool monitoring
- 4. Performance standard: 65 residential gallons/capita/day





- 6. Seasonal limits on nonessential outdoor water use
 - Calendar or stream flow trigger




- 7. Water conservation requirements
 - Water audits, leak detection, metering, pricing, residential and public sector including municipal buildings
- 8. Water withdrawal increases that exceed baseline
 - Offset Feasibility Study



Limits on Nonessential Outdoor Water Use

Permit Requirement

Water Use Restriction Allowance on Withdrawals




- If below 65 RGPCD, permittee implements their own plan with DEP minimums of nonessential outdoor water use from 9 am to 5 pm.
- Exemptions may apply to communities with seasonal populations and/or water supply reservoirs.

Limits on Nonessential Outdoor Water Use

Permit Requirement

Water Use Restriction Allowance on Withdrawals



- If below 65 RGPCD, permittee implements their own plan with DEP minimums of nonessential outdoor water use from 9 am to 5 pm.
- Exemptions may apply to communities with seasonal populations and/or water supply reservoirs.

- 1. Surface water and groundwater source protection
- 2. Firm yield analysis for PWS surface water impoundments
- 3. Wetlands and vernal pool monitoring
- 4. Performance standard: 65 residential gallons/capita/day





- 6. Seasonal limits on nonessential outdoor water use
 - Calendar or stream flow trigger



- 7. Water conservation requirements
 - Water audits, leak detection, metering, pricing, residential and public sector including municipal buildings
- 8. Water withdrawal increases that exceed baseline
 - Offset Feasibility Study



- 1. Surface water and groundwater source protection
- 2. Firm yield analysis for PWS surface water impoundments
- 3. Wetlands and vernal pool monitoring
- 4. Performance standard: 65 residential gallons/capita/day





- 6. Seasonal limits on nonessential outdoor water use
 - Calendar or stream flow trigger



- 7. Water conservation requirements
 - Water audits, leak detection, metering, pricing, residential and public sector including municipal buildings
- 8. Water withdrawal increases that exceed baseline
 - Offset Feasibility Study



Baseline Water Use

Whichever is greatest:

- 2005 water use
- 2003 2005 average water use, or
- registered withdrawal
- First year exceeding baseline, permittee must develop an Offset Feasibility Study and conduct an analysis of the cost effectiveness of mitigations
- Second year exceeding baseline, permittee must implement selected mitigations

Stream Flow Criteria

Fluvial Fish Relative Abundance

Abditaditec				
Biological Category (BC)	August Percent Alteration			
1	< 5%			
2	< 15%			
3	< 35%			
4	< 65%			
5	> 65%			

	% allowable alteration of estimated unimpacted median flow*				
Flow Level (FL)	AUG	ОСТ	JAN	APR	
1	< 5%	< 5%	< 5%	< 5%	
2	< 15%	< 5%	< 5%	< 5%	
3	< 35%	< 15%	< 15%	< 15%	
4	Feasible mitigation and improvement				
5					

- Existing PWS with alteration levels higher than those shown on the chart will be required to maintain and where feasible improve their flow level.
- *Surface water supplies will be evaluated through a separate metric.

Tier Permit Review

Tier 1 Review

No increase requested, no increase above baseline

Tier 2 Review

 Increase above baseline use or increase resulting in less than 5% additional alteration to estimated unaffected flow and would not change biological category or flow level

Tier 3 Review

 Increase would alter estimated unaffected flow by more than 5% and/or would result in a change in biological category or flow level

Tier 1 Review / Permit Conditions

Scenario 1: No increase in withdrawal

(no increase above baseline annual volume)

Existing permit conditions 1 thru 8 apply

In Flow Level 4 or 5, or in the presence of a coldwater fishery resource:

Conduct a pumping optimization evaluation

Tier 2 Review / Permit Conditions

Scenario 2: Withdrawal increase ...

- less than 5% simulated unaffected flow and
- maintains BC/FL stream category flow threshold

- Permit conditions 1 thru 8 apply
- In a coldwater fishery resource*, consultation with DEP/other agencies required to scope potential mitigations measures for evaluation**
- Conduct and submit an Offset/Mitigation Study
- Permittee may get credit for mitigation already implemented
- Mitigation requirements subject to DEP annual review

*Consultation may also be required in Flow Level 4 & 5

**Potential mitigations based on DEP's offset feasibility guidance, NEWWA & MWWA Toolbox

Tier 3 Review / Permit Conditions


Scenario 3: Withdrawal increase ...


- exceeds 5% simulated unaffected flow threshold or
- exceeds BC/FL stream category flow threshold

A water withdrawal increase may be allowed for Water Management Act considerations provided that certain conditions are met*

- Conduct and submit an Alternative Analysis
- Permit conditions 1 thru 8 apply
- Consultation with DEP/other agencies required to scope potential mitigation measures for evaluation
- Conduct and submit an Offset/Mitigation Study
- Permittee may get credit for mitigation already implemented
- Mitigation requirements subject to DEP annual review

- *Conditions such as:
- -No alternative
- Water Needs Forecast
- -WRC Water Conservation Standards





Mitigation Conditions by Categories

Water Supply Related

 Adopt more strict nonessential, outdoor water use restrictions

(e.g., Seasonal cap, Ipswich Basin restrictions, etc.)

- Private well bylaw
- Irrigation sprinkler regulation
- Conservation rate structure
- Enterprise account
- Water banking
- Stretch code water efficiency (e.g., 60 rgpcd)
- Other

Physical Habitat of Stream

- Streambank restoration
- Increase fish passage
- Culvert replacement
- Stream buffers
- Dam removal
- Instream habitat work
- Install and monitor a staff gage
- Support a USGS stream gage
- Land acquisition / CR
- Other

Water Quality / Municipality

- Stormwater bylaw
- Stormwater utility district
- Mitigation fund
- Land acquisition / CR
- Land use protections
- Reduce I/I
- Wastewater reuse/return
- Other

Other entities involved

Questions for Consideration:

- 1. Feasible Mitigation and Improvement for Flow Levels 4 and 5:
 - a) How can we define "feasible mitigation and improvement"?
 - b) For Tier 1 (no increase in withdrawal), how do the WMA permit requirements and NPDES MS4 requirements in municipalities help to satisfy the goal of feasible mitigation and improvement?

Questions for Consideration:

2. Offsets and Mitigation:

- a) What are your thoughts on the desktop pumping optimization evaluation (Tier 1) requirement?
- b) What should be the goal of offsets and mitigation (Tier 2 and Tier 3)?
- c) How can we make mitigation more measureable and commensurate to impact (i.e., rank by location, level of impact, etc)?